

PD 82013S

Project:

Location:

Fixture Type:

Catalog Number:

## **AVAILABLE FINISHES:**



# **Double Bubble**

PD-82013S

#### PRODUCT DESCRIPTION

Like a minimalist take on a crystal ball, these pendant's laser etched orbs are installed in various arrangements on one canopy to create an artful statement as well as deliver amplelighting to spaces throughout a home or business.

# **FEATURES**

- Driver concealed within the canopy
- Laser etched K9 crystal spheres
- Thin powered aircraft cables provide an ultra clean look for adjustable suspension height
- NEC CODE (314.24) requires that ceiling outlet boxes in the U.S. support up to 50 lbs.
- This fixture exceeds 50 lbs. and must be installed using a U.L. listed outlet box approved for up to 100, 200, and 300 lbs. respectfully, or supported independently of the outlet box

## **SPECIFICATIONS**

Rated Life 50000 Hours

Standards ETL, cETL, Damp Location Listed

 Input
 120-277V,50/60Hz

 Dimming
 ELV, 0-10V, TRIAC

 Color Temp
 3000K

 CRI
 90

Construction Die cast aluminum body with laser etched glass shade


# REPLACEMENT PARTS

RPL-GLA-82005 - Glass

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
PD-82013S 20" - 13	3000K 90	41W	3445	AB Aged Brass
Lights	3000K 90	41W	3445	BK Black

Example: PD-82013S-BK

For custom requests please contact customs@modernforms.com



PD-82025S

Project:

Location:

Fixture Type:

Catalog Number:

## **AVAILABLE FINISHES:**





# **Double Bubble**

PD-82025S

#### PRODUCT DESCRIPTION

Like a minimalist take on a crystal ball, these pendant's laser etched orbs are installed in various arrangements on one canopy to create an artful statement as well as deliver amplelighting to spaces throughout a home or business.

# **FEATURES**

- Driver concealed within the canopy
- Laser etched K9 crystal spheres
- Thin powered aircraft cables provide an ultra clean look for adjustable suspension height
- NEC CODE (314.24) requires that ceiling outlet boxes in the U.S. support up to 50 lbs.
- This fixture exceeds 50 lbs. and must be installed using a U.L. listed outlet box approved for up to 100, 200, and 300 lbs. respectfully, or supported independently of the outlet box

## **SPECIFICATIONS**

Rated Life 50000 Hours

Standards ETL, cETL, Damp Location Listed

 Input
 120-277V,50/60Hz

 Dimming
 ELV, 0-10V, TRIAC

 Color Temp
 3000K

 CRI
 90

Construction Die cast aluminum body with laser etched glass shade


# REPLACEMENT PARTS

RPL-GLA-82005 - Glass

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
<b>PD-82025S</b> 28" - 25	3000K 90	82W	7112	AB Aged Brass
Lights	3000K 90	82W	7112	BK Black

Example: PD-82025S-BK

For custom requests please contact customs@modernforms.com



PD-82041S

Project:

Location:

Fixture Type:

Catalog Number:

## **AVAILABLE FINISHES:**





# **Double Bubble**

PD-82041S

#### PRODUCT DESCRIPTION

Like a minimalist take on a crystal ball, these pendant's laser etched orbs are installed in various arrangements on one canopy to create an artful statement as well as deliver amplelighting to spaces throughout a home or business.

# **FEATURES**

- Driver concealed within the canopy
- Laser etched K9 crystal spheres
- Thin powered aircraft cables provide an ultra clean look for adjustable suspension height
- NEC CODE (314.24) requires that ceiling outlet boxes in the U.S. support up to 50 lbs.
- This fixture exceeds 50 lbs. and must be installed using a U.L. listed outlet box approved for up to 100, 200, and 300 lbs. respectfully, or supported independently of the outlet box

## **SPECIFICATIONS**

Rated Life 50000 Hours

Standards ETL, cETL,Damp Location Listed

 Input
 120-277V,50/60Hz

 Dimming
 ELV, 0-10V, TRIAC

 Color Temp
 3000K

 CRI
 90

Construction Die cast aluminum body with laser etched glass shade

# REPLACEMENT PARTS

RPL-GLA-82005 - Glass

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
<b>PD-82041S</b> 36" - 41	3000K 90	123W	10668	AB Aged Brass
Lights	3000K 90	123W	10668	BK Black

Example: PD-82041S-BK

For custom requests please contact customs@modernforms.com